

## Top Tips You Can Apply Immediately to Projects – Highlights from the RE'13 Tutorials

### **Agenda:**

6 tutorial overviews  
Save questions for the end!

Implement Visual Models for Software Requirements Immediately (Full Day)	Joy Beatty and/or James Hulgan
Writing Good Requirements (Full day)	Sarah Gregory
Requirements Quality and Productivity Improvement Based on Example Usage	Marcelo Tueiv, Marcelo do Carmo Coelho, Erica Mourão da Silva
Observational and experimental case study research in requirements engineering: Methodology and Examples (Half day)	Roel Wieringa
Model-Based Systems Requirements (Half day - 3 hours).	Bruel Jean-Michel and Joao Araujo
Applying Model Driven Engineering and Domain Specific Languages to Requirements Engineering	Bruce Trask and Angel Roman

The diagram illustrates a network of requirements for an e-commerce system. The central node is "Seilevel requirements defined". Other nodes include "Wish List", "View Lists", "Create Account", "Account maintenance", and "Manage Account". Sub-nodes for "Account maintenance" include "Remove spam", "Payment", "Password reset", "Register at checkout", "Load monitoring", and "Site language". Sub-nodes for "Create Account" include "Purchase for person" and "Register at save list".

**Two Requirements Models Everyone Should Use**  
IEEE RE'13 Micro Tutorial

© Seilevel, Inc. All rights reserved.

**PMI** Project Management Institute  
**iIBA** Endorsed Education Provider™


Here's what you're going to get

- ✓ 2 Models: Process Flows and RMMs
- ✓ For each of the models, you will learn:
  - How To Create
  - Uses
  - Examples
- ✓ How to incorporate requirements derived from other models

© Seilevel, Inc. All rights reserved.

**Seilevel**  
requirements defined

## Process Flow




- Show business processes, not system processes (but you can make System Flows too)
- Use in elicitation sessions
- Derive requirements from steps

© Seilevel, Inc. All rights reserved.

Seilevel  
requirements defined


## Process flows have levels: L1, L2, and L3



© Seilevel, Inc. All rights reserved.

Seilevel  
requirements defined


## Example L1 Process Flow



© Seilevel, Inc. All rights reserved.



## Example L2 Process Flow



© Seilevel, Inc. All rights reserved.



# Requirements Mapping Matrix (RMM)


L1 Process Step	L2 Process Step	L3 Process Step	REQID	Requirement	Business Rule 1	Business Rule 2

- Organize your requirements by other models
- Derive requirements from other model components
- Remember to keep it up to date

© Seilevel, Inc. All rights reserved.



## Create an RMM to map process steps to requirements




- Add your steps to the matrix
- Add your requirements to the matrix

L1 Process Step	L2 Process Step	REQID	Requirement
1. Add item to cart	1. Select criteria for browsing	REQ001	System shows user all items available in selected category
1. Add item to cart	2. Choose filters to narrow results	REQ002	System shows user all items available in the selected category within the range of the filter selected
1. Add item to cart	2. Choose filters to narrow results	REQ003	System gives option to save filters for future browsing
1. Add item to cart	2. Choose filters to narrow results	REQ004	System does not display filters for categories user already selected during browsing
1. Add item to cart	3. Select item	REQ005	System displays item page when user selects an item
1. Add item to cart	4. Have size?	REQ006	System shows available sizes for the item on item page
1. Add item to cart	4. Have size?	REQ007	System shows sizes that are not in inventory but are still available for backorder
1. Add item to cart	5. Add to cart	REQ008	System adds item to cart for duration of session
1. Add item to cart	5. Add to cart	REQ009	System stores items in cart for when user returns to site

© Seilevel, Inc. All rights reserved.



# Adding Columns for Elements of Objectives Models Help You Control Scope



Objective	Feature	1 Process Step	L2 Process Step	REQID	Requirement
Reduce Cart Abandonment by 50%	Simplified Checkout	Add item to cart	1. Select criteria for browsing	REQ001	System shows user all items available in selected category
Reduce Cart Abandonment by 50%	Simplified Checkout	Add item to cart	2. Choose filters to narrow results	REQ002	System shows user all items available in the selected category within the range of the filter selected
Reduce Cart Abandonment by 50%	Simplified Checkout	Add item to cart	2. Choose filters to narrow results	REQ003	System gives option to save filters for future browsing
Reduce Cart Abandonment by 50%	Simplified Checkout	Add item to cart	2. Choose filters to narrow results	REQ004	System does not display filters for categories user already selected during browsing
Reduce Cart Abandonment by 50%	Simplified Checkout	Add item to cart	3. Select item	REQ005	System displays item page when user selects an item
Reduce Cart Abandonment by 50%	Simplified Checkout	Add item to cart	4. Have size?	REQ006	System shows available sizes for the item on item page
Reduce Cart Abandonment by 50%	Simplified Checkout	Add item to cart	4. Have size?	REQ007	System shows sizes that are not in inventory but are still available for backorder
Reduce Cart Abandonment by 50%	Simplified Checkout	Add item to cart	5. Add to cart	REQ008	Item is added to cart for duration of session
Reduce Cart Abandonment by 50%	Simplified Checkout	Add item to cart	5. Add to cart	REQ009	Item is stored in cart whenever user returns to site

© Seilevel, Inc. All rights reserved.



## Take-away: RML Quick Reference

**Seilevel**  
requirements defined

### RML® Quick Reference

RML™ is a language for modeling software requirements to organize and communicate large quantities of information, help identify missing requirements, give context to individual details within the overall collection of requirements, and represent different views of requirements details.

<p><b>Objectives Models</b></p> <p><b>Business Objectives Model (BOM)</b> A diagram that identifies the value of a project. Use when new functionality is being added to define and control scope.</p> <p><b>Objective Chain</b> A tree structure that measurably links features to business objectives. Use with BOM to select only the features that contribute the most value.</p> <p><b>Key Performance Indicator Model (KPRM)</b> A label on Process or System Flows that associates metrics (KPIs) to business processes to evaluate the performance of the processes. Use it where existing processes or systems are in place in order to maintain or improve overall business throughput.</p> <p><b>Feature Tree</b> A tree structure that shows all features organized into logical groupings. Use to communicate the full set of features in scope for a project.</p> <p><b>Requirements Mapping Matrix (RMM)</b> A matrix that maps requirements and business rules to a model (a Process Flow). Use to organize group information in a more easily consumable way.</p>	<p><b>People Models</b></p> <p><b>Org Chart</b> A diagram that shows all people or roles within an organization and how they relate to one another. Use to identify all stakeholders who might use the system or have requirements.</p> <p><b>Process Flow</b> A diagram that shows the business process steps people execute. It shows the sequence of activities and decisions.</p> <p><b>Use Case</b> Formatted text that describes the interactions between a user and a system. It is used to discover the functional requirements for each step of the interaction.</p> <p><b>Roles and Permissions Matrix</b> A matrix that defines the types of roles and their associated permissions to execute operations in the system. Use it to define security at the operation or menu level.</p>
--	---

© Seilevel, Inc. All rights reserved.





## Landing Zone

Copyright © 2013, Intel Corporation  
All rights reserved

Contact: sarah.c.gregory@intel.com

### The Landing Zone

A Landing Zone is a table that defines a “region” of success for a product or project

**The rows** of the table contain the subset of requirements that directly define success or failure (*not* all the requirements)

**The columns** of the table contain a range of performance levels; usually, a Landing Zone covers the range between great success (Outstanding) and failure avoidance (Minimum)

Landing Zones can be used in agile development to help define success of an iteration or Scrum sprint

**Landing Zones focus attention on what will create success**



## Landing Zone Usage

Landing Zones are useful for several things:

- **Gain explicit consensus** at the start of a project on the definition of success
- **Quantify the achievement levels required** as an input to feasibility and risk analysis
- **Drive tradeoff discussions** and decision making throughout the project
- **Monitor and communicate** product attribute status to decision forums and management during development

15

Copyright © 2010 Intel Corporation. All rights reserved.



## Landing Zone Usage

Landing Zones help clarify decision authority for a team:

Decisions that do not violate any row of the LZ are made by the team as a normal part of their work

- So long as the team meets all LZ rows, that is success

Any decision that would cause any LZ row to be violated requires ratification from a higher authority

- This would include falling below Minimum or a decision to pursue something beyond Outstanding

**Landing Zones can be created for platforms, components, service offerings, user experiences, projects, etc.**

16

Copyright © 2010 Intel Corporation. All rights reserved.



## Exercise 4

### Creating a Landing Zone

#### Instructions:

1. Work individually or in small teams
2. Create a landing zone for your next car purchase, vacation or similar item of your choice; try to include some functions and constraints in addition to rows describing qualities and performance
3. Be ready to share your work with the class when done

**Skill taught: Create a simple landing zone for a product or project**

17

Copyright © 2010 Intel Corporation. All rights reserved.



## Landing Zone Length

### A good Landing Zone is short enough to be comprehended

- A reasonable guideline is two dozen rows at most, and one dozen is better
- The top-level Landing Zone contains only those topics that must be reviewed regularly by upper management
- Additional “child” Landing Zones can capture details and data on other topics; Tabs of a spreadsheet work well for this

Landing Zone format may provide enough data for precedented, low-risk requirements, but *augment Landing Zone entries with full requirements statements in a separate specification when needed*

18

Copyright © 2010 Intel Corporation. All rights reserved.



## Example: Car Purchase Landing Zone

Attribute	Minimum	Target	Outstanding
Price	\$27000	\$20000	\$17,500
Mileage (City)	18mpg	25mpg	35mpg
Seating	4 adults	5 adults	6 adults
Interior Noise at 65 mph	74dBA	65dBA	55dBA
Projected 3-year Maintenance Cost	\$3000	\$2000	\$1500




## Requirements based on examples IBM Brazil - Requirements Center of Competence

Marcelo Tueiv – [mtueiv@br.ibm.com](mailto:mtueiv@br.ibm.com)  
 Erica Mourão da Silva – [ericams@br.ibm.com](mailto:ericams@br.ibm.com)  
 Marcelo do Carmo Coelho – [mcarmo@br.ibm.com](mailto:mcarmo@br.ibm.com)



**How to be more productive / improve quality with:**

- Time to Market / Cost Oriented?
- Different Project Approaches ? (e.g.: Smart Commerce + AD)
- Customer Methodologies?
- Industry & Offering Knowledge needed?
- Software Acquisitions?
- Suppliers integrations?
- One of a Kind Projects?
- Writing Communication Issues?
- Hiring New Employees every week?



Especificação de Requisitos		IBM
Nome do Documento	Titulo	1.0.0
Especificação de Caso de Uso: <Nome do Caso de Uso>		
<p>Este documento descreve os requisitos funcionais e não funcionais de um sistema de informação. O objetivo deste documento é especificar os requisitos de um sistema de informação, de modo a garantir que o sistema desenvolvido atenda às necessidades dos usuários e dos stakeholders.</p>		
<p><b>1.1. Introdução</b></p> <p>1.1.1. Objetivo</p> <p>1.1.2. Escopo</p> <p>1.1.3. Pré-condições</p> <p>1.1.4. Referências</p> <p>1.1.5. Visão Geral</p> <p><b>2. Breve Descrição</b></p> <p><b>3. Diagrama de Caso de Uso</b></p> <p><b>4. Anexos</b></p>		
Revisão	Descrição	Page

- Templates are white boards
  - Try create Performance Rqmt from the scratch
  - Try create Report UC from the scratch
- New Employees without robust guidance
  - Training is not enough
- Teams take time to establish the same level of granularity / quality
- Methods Examples are generic / out of a Context
- Lot of time spent in recurrent Requirements

## Example Approach



- Example centered
- Approach focused on Reuse of **well established / robust** Examples
- Not focused in cover all scenarios, but to be used as **reference**
- Implements our guidelines
- Recurrent Requirements** (ex.: Login, Report, Search, Usability etc)
- Use of Requirements Techniques to establish **good examples**
  - Questionnaires, Storyboards / Sketchs, UML Diagrams, Quality Requirements Syntaxes
- Simple to use**




23

Improve Quality & Productivity

## Use of RE & Reuse Approaches




1. Patterns
2. Use Case Fragments
3. Feature Model
4. Industry Frameworks
5. Visual Modeling
6. Requirements Anti-Patterns
7. Asset Based
8. Others (e.g.: Problem Frames)



24

**Plan**

1. Understand Context / Identify Issues
2. Define Goals
3. Define Scope & Approaches
4. Analyze Return of Investment
5. Pilot Project
6. Define Detailed Plan
7. Train Requirements Engineers in Reuse
8. Define Tools / Process
9. Define Rewards Program
10. Define Measurements



**As an Asset Consumer:**

- Browse Assets
- Reuse Assets
- Subscribe to Assets
- Provide asset feedback using ratings and comments

**As an Asset Producer:**

- Create Assets
- Delete Assets
- Update Assets
- Monitor asset feedback and usage
- Ensure assets are valuable and of high quality

Blue Sheets are used by practitioners to capture individual contribution on project assignments – The results are summarized in their Blue Cards



### Blue Sheets

- Document the outcomes of a practitioner's deliverable assignments
- Require self-assessment of four key factors
  - Quality
  - Cycle Time
  - Speed
  - Reuse
- Are validated by the practitioner's project lead
- Earn Blue Card Points based on meeting or beating plan expectations

### Blue Cards

- Aggregate completed Blue Sheets from the prior six months
- Quantify a Practitioner's contribution to the business – across multiple projects – in terms of Quality, Cycle Time, Speed and Reuse
- Highlight achievement relative to the broader organization, based on Blue Card Points earned
- Provide an environment where individual accomplishments can be distinguished



+3 Blue Card points for each Rated Component reused
+2 Blue Card points for each Reviewed Component reused
+1 Blue Card point for any other asset reused


27

Requirements based on examples - Adoption Plan



### Do – For Each Type of Requirements


1. Define Examples Meta model
2. Create Requirements Guideline
3. Create Reuse Taxonomy (recurrent reqmnts)
4. Requirements harvest (old projects)
5. Review/Create Examples
6. Package as Asset and Submit for Review
7. Train BAs
8. New Contributions



28

**Do – For Each Type of Requirements**

1. Define Examples Meta model
2. Create Requirements Guideline
3. Create Reuse Taxonomy (recurrent reqmnts)
4. Requirements harvest (old projects)
5. Review/Create Examples
6. Package as Asset and Submit for Review
7. Train BAs
8. New Contributions



29


- Example
- Basic details
- Applicability
- Questionnaire
- Discussion
- UML Diagrams
- Sketch / Storyboard
- Anti Patterns
- Considerations for development / testing
- Related Examples



30

**Do – For Each Type of Requirements**

1. Define Examples Meta model
2. Create Requirements Guideline
3. Create Reuse Taxonomy (recurrent reqmnts)
4. Requirements harvest (old projects)
5. Review/Create Examples
6. Package as Asset and Submit for Review
7. Train BAs
8. New Contributions




•Definition of

- Style
- Granularity
- Syntax
- Implement Quality concerns (ambiguity, traceability, testability, completeness etc)
- Standardization
- Other concerns for each type of requirement


•Will be used as base for Requirements QA Checklist

•Robust Guidelines provide **Guidance** to Requirements team about Quality Requirements




**Do – For Each Type of Requirements**

1. Define Examples Meta model
2. Create Requirements Guideline
3. Create Reuse Taxonomy (recurrent reqmnts)
4. Requirements harvest (old projects)
5. Review/Create Examples
6. Package as Asset and Submit for Review
7. Train BAs
8. New Contributions




**Do – For Each Type of Requirements**

1. Define Examples Meta model
2. Create Requirements Guideline
3. Create Reuse Taxonomy (recurrent reqmnts)
4. Requirements harvest (old projects)
5. Review/Create Examples
6. Package as Asset and Submit for Review
7. Train BAs
8. New Contributions



**Do – For Each Type of Requirements**

1. Define Examples Meta model
2. Create Requirements Guideline
3. Create Reuse Taxonomy (recurrent rqrmnts)
4. Requirements harvest (old projects)
5. Review/Create Examples
6. Package as Asset and Submit for Review
7. Train BAs
8. New Contributions



35

**Questionnaire:**

1. What's the max number of pages?
2. What 's behaviour when no items are found? Is it expected to hide paging options?
3. What shortcuts can be used to navigate in pages?

**Discussion:**

The navigation bar tells the users the most important information about the list; how many items there are, how many they see now and how to get to the rest. By placing the navigation below the list it is there when users need it most: after scanning all items on the page. Although paging is a very common and accepted way of interacting, the arrival of Ajax technology has introduced new possibilities where paging is no longer needed. All results are simply shown but only loaded as the user scrolls down. See for example the [Apple store's software section](#) or [Dzone](#)


**Considerations for development / testing:**

- Deletions of records can bring unexpected behavior of paging. More attention for test these situations: deletion of 1<sup>st</sup> record, middle or last record.

36 Source: van Welle, 2005 – Wellie.com


### Check – For Each Project

1. Collect Rqrmnts Quality & Examples Metrics
2. Collect Examples Issues/Defect
3. Evaluate Examples Usage
4. Evaluate Examples Contribution
5. Analyze Examples Effectiveness
6. Define Improvement Action Plan



© Copyright IBM Corporation 2012. All rights reserved. The information contained in these materials is provided for informational purposes only, and is provided AS IS without warranty of any kind, express or implied. IBM shall not be responsible for any damages arising out of the use of, or otherwise related to, these materials. Nothing contained in these materials is intended to, nor shall have the effect of, creating any warranties or representations from IBM or its suppliers or licensors, or altering the terms and conditions of the applicable license agreement governing the use of IBM software. References in these materials to IBM products, programs, or services do not imply that they will be available in all countries in which IBM operates. Product release dates and/or capabilities referenced in these materials may change at any time at IBM's sole discretion based on market opportunities or other factors, and are not intended to be a commitment to future product or feature availability in any way. IBM, the IBM logo, Rational, the Rational logo, Telelogic, the Telelogic logo, and other IBM products and services are trademarks of the International Business Machines Corporation, in the United States, other countries or both. Other company, product, or service names may be trademarks or service marks of others.

## Observational and experimental case study research in RE: Methodology and Examples



### What is a case study

- A case is a real-world sociotechnical system
  - Observational case studies (only observe)
  - Technical action research (intervene, using a new technology, and observe)

- You can generalize from a single case study by
  - Observe architecture of a case;
  - Assess architectural similarity between cases and
  - Estimate whether the mechanism in case with similar architecture, will have similar effects.
  
- The generalization will be middle-range
  - Not all other cases
  - Realistic abstractions

- Case architecture
  - Components
  - Capabilities
  - Mechanisms
- Mechanisms do not occur in isolation
  - Each mechanism may be understood in isolation
  - No universal law of addition of mechanisms
  - Assess combined effect case by case

1. Identify the boundary of the case
  - What kind of case? Population
  - What internal structure? (Architecture)
2. State your research questions in advance
3. Decide how to collect data in advance
4. Decide how to analyze the data in advance
5. When analyzing:
  - Describe architecture and phenomena
  - Explain (in terms of mechanisms)
  - Generalize (to cases with similar architecture)



Universit  de Toulouse



FACULDADE DE CI NCIAS E TECNOLOGIA  
UNIVERSIDADE NOVA DE LISBOA



21st IEEE International  
Requirements Engineering Conference  
July 15th-19th, 2013, Rio de Janeiro, Brasil.

# Model-Based Systems Requirements

Jean-Michel Bruel  
Jo o Ara jo



RE'2013 44

**Example:**

UI0001 – Paging:

The system must present the results grouped in pages with a fixed number of items and allow the users to move from one page of items to another

It will be provided a direct link to a particular page and links to the next/previous page that allow stepping through the pages. Also show the total number of items and use a title to say what kind of items they are.

**Sketch:**

**Applicability:** Often users need to go through a large list of items. This pattern is applicable when the items are too numerous to fit on one page. The items are typically ordered and the users are likely to find their desired item somewhere near the start, for example in [Search Results](#) where this pattern is nearly always used. Paging is also often used together with a [List Builder](#), for example in an web-based e-mail application. The number of items is typically at 10 to 200 items. The 'Items' can be anything such as e-mail headers, names, photos, phone numbers and so on.

45 Source: van Welle, 2005 – Welle.com

## A Complex System

- ▶ Set of human and material elements composed of various technologies
  - Computer, Hydraulic, Electronic,...
- ▶ Integrated to provide services to its environment corresponding to the system finality
- ▶ Interacting between themselves and the environment

A complex system is very different from a simple software system




RE'2013

46


# Systems of Systems

- ▶ A system
  - Should manage interactions between parts
  - Support expected behavior
  - Handle unexpected ones



RE'2013 47


# System Modeling




RE'2013

48


# SE practices for modeling systems



# KAOS main model elements




# SysML 1.3 diagrams



RE'2013

51


# RequirementDiagrams (req)




RE'2013

52

# Requirement Derivation



# Reducing ambiguity




# Mapping KAOS models into SysML models

- ▶ Mapping Modeling concepts
  - Goal → <<requirement>>
  - Requirement → <<requirement>> (system)
  - Expectation → <<requirement>> (user)
  - Resolutions → <<requirement>> (system or user)
  - Entity → Block
  - Operation → activity or Block operation
  - Environment Agents → Actors
  - System Agents → Blocks/components
  - ...
- ▶ Relationships
  - Decomposition
    - Or → multiple <<refine>>
    - And → composition
  - Concerns → <<satisfy>>
  - ...
- ▶ No direct mapping
  - Obstacles
  - Conflicts

RE'2013

55


# Mapping KAOS/SysML: example



RE'2013

56


# Transformation Framework



RE'2013

57


# Cable TV (Requirements)



RE'2013

58

## Cable TV (Traceability links)



RE'2013

59



## Conclusions

- ▶ KAOS
  - Goal-oriented modeling language
  - Special role at Requirements elicitation
- ▶ SysML is:
  - a specific language for complex systems
  - strongly UML-Based
  - focusing on analysis
  - SysML is not:
    - a method
    - just a UML profile
    - sufficient in itself
- ▶ Synergy between KAOS and SysML!
  - Model transformations

RE'2013

60

# Applying Model Driven Engineering and Domain Specific Languages to Requirements Engineering




Refinement



Permission to make digital or hard copies of part or all of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, to republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee.  
SPLC - Vol. 8, September 02 - 07 2012, Salvador, Brazil  
Copyright 2012 ACM 978-1-4503-1095-6/12/09 \$15.00.

## Requirements Engineering

*Bruce Trask  
Angel Roman  
MDE Systems*





**MDE SYSTEMS**

© Copyright MDE Systems 2011

61

## Summary




**MDE SYSTEMS**

© Copyright MDE Systems 2011

62


# Synergy / Holism



© Copyright MDE Systems 2011

63


# Language and Platform



© Copyright MDE Systems 2011

64

## Language and Platform – where we are now



## What's underneath the problems

- Language technology has not kept pace with platform technology<sup>1</sup>
- Insufficient *linguistic power* to tackle platform, domain and requirement complexity
- Lack of *tools* to deal with increased complexity

<sup>1</sup> Douglas C. Schmidt IEEE Computer Magazine February 2006

## Solution

- Leverage recent critical innovations to provide a quantum leap of language technology and tools to overcome the complexity gap



© Copyright MDE Systems 2011

67

## Orders of Magnitude


- 1000x more processing power
- 1000x more dynamic memory
- 1000x more disk space
- 1000x more power efficiency
- 1000x smaller
- 15 orders of magnitude



© Copyright MDE Systems 2011

68

## Rote vs. Creative Code



© Copyright MDE Systems 2011

69

## Non Software Example “Domain Independent”



© Copyright MDE Systems 2011

70

## Non Software Example “Domain Specific”



© Copyright MDE Systems 2011

71


## Non Software Example “Domain Specific”



© Copyright MDE Systems 2011

72

# Language Workbench



© Copyright MDE Systems 2011

73

**Questions for any of our  
tutorial presenters?**